GYPSOMAN

PLASTER BOARD





GYPSOMAN Plasterboards are durable, flexible gypsum boards ideal for modern construction uses like ceilings and wall linings. Made from 100% natural, non-combustible gypsum, they are easy to work with and support conventional paint, ceramics, and standard fixtures for electrical and plumbing.













Length (mm)	Indian standard 1830 - GCC standard 2400 on request: any size between 1800 - 3500	
Width (mm)	Indian standard 1220 - GCC standard 1200 ask our team for special width sizes	
Thickness (mm)	standard 12.50 on request: 7 / 8 / 9 / 9.5 / 12 / 15 / 18	
Edge	Tapered: the standard convenient type on request: Squared / Beveled / Round	
Color	Face: Ivory - Back: Grev	

Properties (per 12.5mm)	ASTM 1396:2006 Specifications	BS EN 520:2004 Specifications	GYPSOMAN Specifications
Flexural Strength (N)Longitudinal	≥ 480	≥ 550	≥560
Flexural Strength (N)Transverse	≥ 175	≥ 210	≥210
Nail Pull Resistance (N)	≥ 343	-	≥355
Core Hardness (N)	≥ 49	-	≥60
Core end Hardness (N)	≥ 49	-	≥60
Edge Hardness (N)	≥ 49	-	≥60
Thickness (mm)	± 0.40	± 0.5	± 0.2
Board Length (mm)	± 6.0	0, - 5	0, - 2.0 mm
Board Width (mm)	0, -3.0	0, -4	0, -2.0 mm
End Squareness (mm)	±3.2	≤ 2.5	± 2.0
Weight (kg/m²)			7.5 ± 0.2